POLY CONTROL 2

Registered Trademark of Brewer International

SHAKE WELL BEFORE USING

CLEAN UP: Rinse spray tank after each use and flush thoroughly. Dispose of container in proper manner, do not reuse.

CAUTION: POLY CONTROL 2, diluted or undiluted, is very slippery. Use sand, sawdust or similar absorbent material on any spill, pick up with shovel or dustpan.

CAUTION KEEP OUT OF REACH CHII DRFN Dο take not internally. Avoid eve and skin contact. If contact occurs, flush thoroughly with water. If irritation persists. consult а physician. Read and follow all label directions and cautions on all products used. We warrant that this product chemical conforms to the description on the label and is reasonably fit for the purposes set forth on the label when used according to directions under normal use conditions. THERE ARE NO OTHER WARRANTIES **EXPRESSED** WHFTHFR IMPLIED. INCLUDING when used according to directions under normal use conditions. THERE ARE NO OTHER WARRANTIFS WHETHER **EXPRESSED** IMPLIED INCLUDING WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

STICKER, SINKER AND DRIFT Do not add water to container CONTROL AGENT FOR HERBICIDES

PRINCIPLE FUNCTIONING AGENTS:

Polyacrylamide, emulsifiers and ingredients ineffective as spray adjuvants100%

NONIONIC

CAUTION

AVOID EYE AND SKIN CONTACT. DO NOT TAKE INTERNALLY, Keep Out of Reach of Children.

NET CONTENTS:



BREWER International

P.O. BOX 690037 Vero Beach, FL 32969-0037 ©2024 BREWER INTERNATIONAL, INC.

SHAKE WELL **BEFORE USING**

Do not add water to container

AQUATIC SINKING POLY CONTROL 2 will sink spray solutions when used at high rates.

SUGGESTED RATES: Use 0.5 - 2 gallons per 100 gallons of spray solution. Add slowly while agitating 3-4 minutes.

TERRESTRIAL DRIFT CONTROL POLY CONTROL 2 Is formulated to aid control of drift sprav solutions.

SUGGESTED RATES: Use 1-8 ounces per 100 gallons of solution. POLY sprav CONTROL 2 should be added slowly to spray solution while agitating. Allow 3-4 minutes of agitation before spraying: longer agitation will increase viscosity.

Rates can vary dependent nogu pressure. spray solution, wind speed, nozzle selection and configuration.

For sinking, rates can vary with flow of water.

STORAGE AND DISPOSAL: Do not store near heat or open flame. Store original container. Do not reuse empty container. Triple rinse equivalent) then dispose recondition container through the regulations set by local and state authorities.